

AIR SANITIZER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20
CD 2004/3 Page 1 of 14

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

AIR SANITIZER

STATEMENT OF HAZARDOUS NATURE

CONSIDERED A DANGEROUS SUBSTANCE ACCORDING TO DIRECTIVE 67/548/EEC, POINT 4; AND HAZARDOUS ACCORDING TO OSHA 29 CFR 1910.1200 (USA).

SUPPLIER

Company: Double Class (M) Sdn Bhd
Address:
No.14, Jalan 4
Pandan Indah
Kuala Lumpur, 55300
MYS
Telephone: +60 3 4280 9898

CONTACT

National Poisons Center of Malaysia
1800 888 099 (office hours)

MOLECULAR MASS

Molecular mass: Not Applicable

PRODUCT USE

Application is by spray atomisation from a hand held aerosol pack Application is by spray atomisation from a hand held aerosol pack Air sanitiser.

Section 2 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	INT HAZ	%
ethanol EC NO: 200-578-6 R CODES: R11,R36	64-17-5	F+,Xi	40-60
2,4,4'-trichloro-2'-hydroxydiphenyl ether EC NO: 222-182-2 R CODES: R36,R50,R58	3380-34-5	Xi,N	0-1
fragrance hydrocarbon propellant EC NO: 270-704-2 R CODES: R3,R12,R44	68476-85-7.	None	0-1 40-60

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet

Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20

CD 2004/3 Page 2 of 14

Section 3 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Gas.
Mixes with water.

Molecular Weight: Not Applicable
Melting Range (°C): Not Available
Solubility in water (g/L): Miscible
pH (1% solution): Not Applicable
Volatile Component (%vol): Not Available
Relative Vapour Density (air=1): Not Available
Lower Explosive Limit (%): Not Available
Autoignition Temp (°C): Not Available
State: COMPRESSED GAS

Boiling Range (°C): Not Available
Specific Gravity (water=1): <1
pH (as supplied): Not Applicable
Vapour Pressure (kPa): Not Available
Evaporation Rate: Not Available
Flash Point (°C): -81 (propellant)
Upper Explosive Limit (%): Not Available
Decomposition Temp (°C): Not Available

APPEARANCE

Supplied as an aerosol pack. Contents under PRESSURE. Contains highly flammable hydrocarbon propellant.
Highly flammable liquid with a fragrant odour; mixes with water.

Section 4 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

RISK

Irritating to eyes.
Extremely flammable.
Toxic to aquatic organisms.
Risk of explosion if heated under confinement.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.
Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis);

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet

Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20

CD 2004/3 Page 3 of 14

Section 4 - HAZARDS IDENTIFICATION ...

temporary impairment of vision and/or other transient eye damage/ulceration may occur.

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

CHRONIC HEALTH EFFECTS

Principal route of occupational exposure to the gas is by inhalation. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Prolonged exposure to ethanol may cause damage to the liver and cause scarring. It may also worsen damage caused by other agents. Large amounts of ethanol taken in pregnancy may result in "foetal alcohol syndrome", characterised by delay in mental and physical development, learning difficulties, behavioural problems and small head size. A small number of people develop allergic reactions to ethanol, which include eye infections, skin swelling, shortness of breath, and itchy rashes with blisters. 4,4'-dihydroxyphenyl oxide may have effects similar to female sex hormones. Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.

Section 5 - FIRST AID MEASURES

SWALLOWED

Not considered a normal route of entry.

If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

- If swallowed do NOT induce vomiting.
 - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
 - Observe the patient carefully.
 - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
 - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
 - Seek medical advice.
- Avoid giving milk or oils.
Avoid giving alcohol.

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet

Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20

CD 2004/3 Page 4 of 14

Section 5 - FIRST AID MEASURES ...

EYE

If aerosols come in contact with the eyes:

- Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If solids or aerosol mists are deposited upon the skin:

- Flush skin and hair with running water (and soap if available).
- Remove any adhering solids with industrial skin cleansing cream.
- DO NOT use solvents.
- Seek medical attention in the event of irritation.

INHALED

If aerosols, fumes or combustion products are inhaled:

- Remove to fresh air.
- Lay patient down. Keep warm and rested.
- Protheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Treat symptomatically.

For acute or short term repeated exposures to ethanol:

- Acute ingestion in non-tolerant patients usually responds to supportive care with special attention to prevention of aspiration, replacement of fluid and correction of nutritional deficiencies (magnesium, thiamine pyrodoxine, Vitamins C K)
- Give 50% dextrose (50-100 ml) IV to obtunded patients following blood draw for glucose determination.
- Comatose patients should be treated with initial attention to airway, breathing, circulation and drugs of immediate importance (glucose, thiamine)
- Decontamination is probably unnecessary more than 1 hour after a single observed ingestion. Cathartics and charcoal may be given but are probably not effective in single ingestions.
- Fructose administration is contra-indicated due to side effects.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported;

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20
CD 2004/3 Page 5 of 14

Section 5 - FIRST AID MEASURES ...

intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.

- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

Section 6 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

SMALL FIRE:

- Water spray, dry chemical or CO₂

LARGE FIRE:

- Water spray or fog.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
 - May be violently or explosively reactive.
 - Wear breathing apparatus plus protective gloves.
 - Prevent, by any means available, spillage from entering drains or water course.
 - If safe, switch off electrical equipment until vapour fire hazard removed.
 - Use water delivered as a fine spray to control fire and cool adjacent area.
 - DO NOT approach containers suspected to be hot.
 - Cool fire exposed containers with water spray from a protected location.
 - If safe to do so, remove containers from path of fire.
 - Equipment should be thoroughly decontaminated after use.
- When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 100 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- Aerosol cans may explode on exposure to naked flame.
- Rupturing containers may rocket and scatter burning materials.
- Hazards may not be restricted to pressure effects.
- May emit acrid, poisonous or corrosive fumes.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet

Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20

CD 2004/3 Page 6 of 14

Section 6 - FIRE FIGHTING MEASURES ...

Combustion products include
carbon dioxide (CO₂)
other pyrolysis products typical of burning organic material

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Section 7 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.
- Wipe up.
- If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Absorb or cover spill with sand, earth, inert materials or vermiculite.
- If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.
- Collect residues and seal in labelled drums for disposal.

PROTECTIVE ACTIONS FOR SPILL


continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20
CD 2004/3 Page 7 of 14

Section 7 - ACCIDENTAL RELEASE MEASURES ...



From IERG (Canada/Australia)

Isolation Distance

-

Downwind Protection Distance

8 metres

FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills".
LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.
- 5 Guide 126 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

Section 8 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet

Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20

CD 2004/3 Page 8 of 14

Section 8 - HANDLING AND STORAGE ...

- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- DO NOT incinerate or puncture aerosol cans.
- DO NOT spray directly on humans, exposed food or food utensils.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Aerosol dispenser.
- Check that containers are clearly labelled.

STORAGE INCOMPATIBILITY

Incompatible with aluminium. DO NOT heat above 49 deg. C. in aluminium equipment.

Avoid reaction with oxidising agents

STORAGE REQUIREMENTS

Store in an upright position.

Outside or detached storage is preferred.

Store below 38 deg. C.

Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can

- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.
- Store away from incompatible materials.
- Store in a cool, dry, well ventilated area.
- Avoid storage at temperatures higher than 40 deg C.
- Store in an upright position.
- Protect containers against physical damage.
- Check regularly for spills and leaks.
- Observe manufacturer's storing and handling recommendations.

Section 9 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

ODOUR SAFETY FACTOR (OSF)

OSF=0.16 (hydrocarbon propellant)

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20
CD 2004/3 Page 9 of 14

Section 9 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.
The Odour Safety Factor (OSF) is defined as:
 $OSF = \text{Exposure Standard (TWA) ppm} / \text{Odour Threshold Value (OTV) ppm}$
Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV-TWA for example) is being reached, even when distracted by working activities
B	26-550	As "A" for 50-90% of persons being distracted
C	1-26	As "A" for less than 50% of persons being distracted
D	0.18-1	10-50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As "D" for less than 10% of persons aware of being tested

EXPOSURE STANDARDS FOR MIXTURE

"Worst Case" computer-aided prediction of vapour components/concentrations:

Composite Exposure Standard for Mixture (TWA) (mg/m^3): 1831.1688 mg/m^3
If the breathing zone concentration of ANY of the components listed below is exceeded, "Worst Case" considerations deem the individual to be overexposed.
Component Breathing Zone ppm Breathing Zone mg/m^3 Mixture Conc: (%)

Component	Breathing zone (ppm)	Breathing Zone (mg/m^3)	Mixture Conc (%)
hydrocarbon propellant	610.39	1098.7013	60.0
ethanol	389.61	732.4675	40.0

INGREDIENT DATA

ETHANOL:

TLV TWA: 1000 ppm A4 [ACGIH]

TLV TWA: 1000 ppm, 1880 mg/m^3 A4

NOTE: This substance has been classified by the ACGIH as A4 NOT classifiable as causing Cancer in humans

ES TWA: 1000 ppm, 1880 mg/m^3

OES TWA: 1000 ppm, 1920 mg/m^3

MAK value: 500 ppm, 960 mg/m^3

MAK Category II Peak Limitation: For substances with systemic effects and with a half-life in humans of less than two hours.

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet

Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20

CD 2004/3 Page 10 of 14

Section 9 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

Allows excursions of 2 times the MAK value, for 30 minutes (on average), four times per shift.

MAK Group C: There is no reason to fear risk of damage to the developing embryo when MAK and BAT values are observed.

MAK values, and categories and groups are those recommended within the Federal Republic of Germany

Odour Threshold Value: 49-716 ppm (detection), 101 ppm (recognition)

IDLH Level: 3300 ppm (lower explosive limit)

Eye and respiratory tract irritation do not appear to occur at exposure levels of less than 5000 ppm and the TLV-TWA is thought to provide an adequate margin of safety against such effects.

Experiments in man show that inhalation of 1000 ppm caused slight symptoms of poisoning and 5000 ppm caused strong stupor and morbid sleepiness.

Subjects exposed to 5000 ppm to 10000 ppm experienced smarting of the eyes and nose and coughing. Symptoms disappeared within minutes.

Inhalation also causes local irritating effects to the eyes and upper respiratory tract, headaches, sensation of heat intraocular tension, stupor, fatigue and a need to sleep.

At 15000 ppm there was continuous lachrymation and coughing.

2,4,4'-TRICHLORO-2'-HYDROXYDIPHENYL ETHER:

Dusts not otherwise classified, as inspirable dust;

ES TWA: 10 mg/m³

HYDROCARBON PROPELLANT:

hydrocarbon propellant, as liquified petroleum gas

TLV TWA: 1000 ppm, 1800 mg/m³

ES TWA: 1000 ppm, 1800 mg/m³

OES TWA: 1000 ppm, 1750 mg/m³; STEL: 1250 ppm, 2180 mg/m³

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them. DO NOT wear contact lenses.

HANDS/FEET

No special equipment needed when handling small quantities.

OTHERWISE:

For potentially moderate exposures:

Wear general protective gloves, eg. light weight rubber gloves.

For potentially heavy exposures:

Wear chemical protective gloves, eg. PVC. and safety footwear.

OTHER

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Skin cleansing cream.

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet
Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20
CD 2004/3 Page 11 of 14

Section 9 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

- Eyewash unit.
- Do not spray on hot surfaces.

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:
"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the
computer-generated selection:

Substance

ethanol	
BUTYL	A
NITRILE+PVC	A
PE/EVAL/PE	A
NEOPRENE	A
NITRILE	A
PVC	B
NATURAL+NEOPRENE	C
NATURAL RUBBER	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove,
a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis,
factors such as "feel" or convenience (e.g. disposability), may dictate a choice
of gloves which might otherwise be unsuitable following long-term or frequent
use. A qualified practitioner should be consulted.

RESPIRATOR

Respiratory protection may be required when ANY "Worst Case" vapour-phase
concentration is exceeded (see Computer Prediction in "Exposure Standards").

Protection Factor	Half-Face Respirator	Full-Face Respirator
5 x ES	Air-line*	A-2
	-	A-PAPR-2
10 x ES	-	A-3
10+ x ES	-	Air-line**

* - Continuous Flow; ** - Continuous-flow or positive pressure demand

^ - Full-face

The local concentration of material, quantity and conditions of use determine
the type of personal protective equipment required. For further information
consult site specific CHEMWATCH data (if available), or your Occupational
Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal conditions. If risk of overexposure

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet

Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20

CD 2004/3 Page 12 of 14

Section 9 - EXPOSURE CONTROLS / PERSONAL PROTECTION ...

exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection.

Provide adequate ventilation in warehouse or closed storage areas.

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Elevated temperatures.
- Presence of open flame.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

Air Sanitizer

Not available. Refer to individual constituents.

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

ETHANOL:

TOXICITY

Oral (rat) LD50: 7060 mg/kg

Oral (human) LDLo: 1400 mg/kg

Oral (man) TDLo: 50 mg/kg

Oral (man) TDLo: 1.40 mg/kg

Oral (woman) TDLo: 256 mg/kg/12 wks

Inhalation (rat) LC50: 20,000 ppm/10h

IRRITATION

Skin (rabbit):20 mg/24hr-moderate

Skin (rabbit):400 mg (open)-mild

Eye (rabbit):100mg/24hr-moderate

Eye (rabbit): 500 mg SEVERE

2,4,4'-TRICHLORO-2'-HYDROXYDIPHENYL ETHER:

TOXICITY

Oral (rat) LD50: 3700 mg/kg

Inhalation (rat) LC50: > 140 mg/kg*

Dermal (rabbit) LD50: > 6000 mg/kg*

[Van Waters & Rogers]* [Thompson Research] **

IRRITATION

Skin (human):0.75 mg/3d-l- mild

Skin (rabbit): 10% - mild

Eye: SEVERE **

HYDROCARBON PROPELLANT:

No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

Drinking Water Standards:

hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet

Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20

CD 2004/3 Page 13 of 14

Section 12 - ECOLOGICAL INFORMATION ...

Wastes resulting from use of the product must be disposed of on site or at approved waste sites

Section 13 - DISPOSAL CONSIDERATIONS

- Consult State Land Waste Management Authority for disposal.
 - Discharge contents of damaged aerosol cans at an approved site.
 - Allow small quantities to evaporate.
 - DO NOT incinerate or puncture aerosol cans.
 - Bury residues and emptied aerosol cans at an approved site.
-

Section 14 - TRANSPORTATION INFORMATION

Shipping Name: AEROSOLS
Hazard Class: 2.1
UN/NA Number: 1950
Packing Group: None
Labels Required: flammable gas
Additional Shipping Information:
International Transport Regulations:
IMO: 2.1

Section 15 - REGULATORY INFORMATION

RISK

Irritating to eyes.
Extremely flammable.
Toxic to aquatic organisms.
Risk of explosion if heated under confinement.

SAFETY

Avoid exposure - obtain special instructions before use.
To clean the floor and all objects contaminated by this material, use water.
Take off immediately all contaminated clothing.
In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre (show this container or label).
If you feel unwell contact Doctor or Poisons Information Centre (show the label if possible).

REGULATIONS

No data available for ethanol as (CAS: 64-17-5). (CAS: 3380-34-5).
(CAS: 68476-85-7). (CAS: 68476-86-8).

continued...

AIR SANITIZER

ChemWatch Material Safety Data Sheet

Issue Date: Tue 14-Sep-2004

CHEMWATCH 4811-20

CD 2004/3 Page 14 of 14

Section 15 - REGULATORY INFORMATION ...

Section 16 - OTHER INFORMATION

This product contains non-depleting Ozone Substances

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Tue 14-Sep-2004

Print Date: Wed 15-Sep-2004